


Planet R0-plus → 19,8 / 36 x 20 mm | ↓ 16 mm | ≤ 54 dB



Main features

- Seal height up to ↓ 16 mm
- Acoustic insulation up to ≤ 54 dB in case of an optimal sealing (Proof for MF-plus)
- Unilateral and soundless release, silent seal
- Due to parallel drop-down no trailing on the floor
- Automatic compensation at inclined floors
- For double leaf folding doors with flush bolt or driving bar
- High-grade silicone lip, simple lift height adjustment
- Can be shortened up to the next shorter length on stock
- No extra need to cut off silicone at both ends
- 7 years warranty

Versions / options

- Planet R0-plus → FH+RD ≤ 54 dB, fire-retardant + smoke-shielding
- Option Double-shortening → refer to chapter Accessories | TR125
- Special versions on request

Door types with Planet R0-plus




Double leaf doors → refer to chapter Accessories | Flush bolt, drilling

More functions



Technical specifications

Profile material	aluminum, → 19,8 / 36 x 20 mm
Seal profile	high-grade silicone or high-grade self-extinguishing silicone
Seal height	up to ↓ 16 mm
Sound absorption value	up to ≤ 54 dB at 7 mm space to the floor; up to ≤ 50 dB at 14 mm space to the floor
Lift height adjustment	on the release knob with an Allen key 3 mm
Lengths in stock	335, 460, 585, 710, 835, 960, 1085, 1210, 1335, 1460, 1585 mm
Special lengths	on request up to 6000 mm for wing- and sliding doors
Release	unilaterally on hinge side
Can be shortened	up to the maximum of 125 mm (335 mm only 115 mm)
Fastening	from the bottom with screws available with the customer
Frame protector plate	stainless, hammer fixed, 20 x 20 mm
Test approvals	on request






Profile Planet R0-plus




Planet R0-plus, release side



Option: Planet R0-plus with Planet drill hole $\varnothing 5 \times 13$ mm for flush bolt, driving bar rods → refer to chapter Accessories | driving bar rods



Option: Planet R0-DD with Planet drill hole $\varnothing 10$ mm for flush bolt, driving bar rods → refer to chapter Accessories | driving bar rods



Accessories: Planet KR flush bolt, incl. strike plate → refer to chapter Accessories | Flush bolt
Driving bar rods flattened
→ see pages 151 – 161

Order specifications

Planet R0-plus-DD → FH+RD ≤ 54 dB	Prod. code 57xxx-DD*
--	----------------------

* xxx = refer to price list for profile length

Accessories | Options

Planet drill hole $\varnothing 5 \times 13$ mm including plastic guide, for Planet KR and driving bar rods flattened → refer to chapter Accessories Flush bolt, drilling	Prod. code 900190
Planet drill hole $\varnothing 10$ mm	Prod. code 900280
Planet BM floor strikes → refer to chapter Accessories BM	Prod. code 90034x-x Prod. code 90027x-x
Cut the Planet to fix dimension	Prod. code 900200

x-x = Several Planet Floor strikes available in different adjustment range
refer to chapter Accessories | BM

Advertising text



Planet R0-plus → FH+RD (fire-retardant + smoke-shielding) ≤ 54 dB

Automatic door drop-down seal **Planet R0-plus → FH+RD ≤ 54 dB**, for sound protection-, smoke-shielding and fire-retardant doors, release on hinge side with automatic compensation in case of an inclined floor, parallel drop-down, seal height up to **16 mm**. Self-extinguishing silicone lip, fastening on the bottom. Aluminum profile → **19,8 / 36 x 20 mm**.